This comment shows that the query was generated from the Trips Controller Index Action in the Rideshare application. The Marginalia documentation advises against adding unique value components when using Prepared Statements because a unique value will prevent re-use of them. You'll learn about Prepared Statements soon.

Since knowing where the query was generated is extremely useful, this capability was added directly to Rails 7 and is called "Query Log Tags."

Rideshare enables Query Log Tags by setting config.active_record.query_log_tags_enabled to true in config/application.rb. Note that Prepared Statements is incompatible with Query Log Tags (See the Warning in the config.active_record.query_log_tags_enabled section[2]).

For this section, Prepared Statements were disabled in the application by putting prepared_statements = false in config/database.yml.

With Prepared Statements disabled and Query Log Tags enabled, Rideshare will show similar comments to the Marginalia gem in the logged SQL queries. You'll even notice these in the logged SQL in the server log or console log output. For example, notice /*application:Rideshare*/ comment and run the example below from bin/rails console.

```
irb(main):020:0> Trip.first
  Trip Load (0.5ms)  /*application:Rideshare*/ SELECT "trips".*
  FROM "trips" ORDER BY "trips"."id" ASC LIMIT $1  [["LIMIT", 1]]
=>
```

Now you've got a new query observability tool that can help you as you work on improving your application queries.

What are some of the common query problems that can happen?

Common Active Record Problems

The following terminology guide can be used to help learn terms or refresh your knowledge on terms used in this chapter.

Active Record Optimization Terminology



- Normalization — Removing duplication from fields
- Lazy Loading — Loading data "late" and on-demand
- Eager Loading — Loading data "early" or upfront

2. https://edgeguides.rubyonrails.org/configuring.html#config-active-record-query-log-tags-enabled