```
 {                              +
     "ride_details": {          +
         "music_on": true,      +
         "bags_in_trunk": 1,    +
         "water_offered": true+
     }                          +
 }
(1 row)
```

The following SQL file performs a few actions. First you'll create three JSON variables as JSON formatting strings that represent the data source for the additional attributes.

To store the data, you'll modify the Rideshare trips table and add the data column as a new nullable jsonb column. The SQL statement does assume that trips with primary keys 1, 2, and 3 exist. The dollar quoted literal technique and line breaks are used for legibility.

Run these statements from psql:

sql/jsonb_trip_details_multi_insert.sql

```
-- Populate json_string1, json_string2, and json_string3
SELECT $$'{"ride_details":
{"bags_in_trunk": 1, "music_on": true,"water_offered": false}
}'::jsonb$$
AS json_string1 \gset

SELECT $$'{"ride_details":
{"bags_in_trunk": 2, "music_on": true,"water_offered": true}
}'::jsonb$$
AS json_string2 \gset

SELECT $$'{"ride_details":
{"bags_in_trunk": 3, "music_on": false,"water_offered": true}
}'::jsonb$$
AS json_string3 \gset

-- Add the `data` column to the trips table
ALTER TABLE trips ADD COLUMN data jsonb;

-- Insert 3 json blobs from above into the `trips`
-- table, for ids 1, 2, 3
--
-- use UPDATE ... FROM for multi-row update
-- https://stackoverflow.com/a/18799497
UPDATE trips AS t
SET data = c.json_string
from (VALUES
    (:json_string1, 1),
    (:json_string2, 2),
    (:json_string3, 3)
) AS c(json_string, trip_id)
```