highlight - SKIP_LOCKED for VACUUM and ANALYZE[9]). Try running this statement from psql:

sql/vacuum_multiple_skip_locked.sql
```
VACUUM (SKIP_LOCKED) trip_requests, trips;
```

PostgreSQL keeps track of when Vacuum and Analyze are run both automatically and manually.

The following query shows a last_analyzed timestamp for the users table, which is when it had been last vacuumed manually. The timestamp last_auto_analyzed_at shows when the table was analyzed last by Autovacuum.

sql/last_analyzed_pg_stat_all_tables.sql
```
SELECT
  schemaname,
  relname,
  last_autoanalyze,
  last_analyze
FROM pg_stat_all_tables
WHERE relname = 'vehicles';
```

Try running it for the vehicles table. The value for last_analyze may be empty. Run ANALYZE vehicles; and then check the last_analyze value again.

Since PostgreSQL 13, Parallel Vacuum Workers can be configured (See: *Parallel Vacuum in Upcoming PostgreSQL 13*[10]).

The default value for MAX_PARALLEL_MAINTENANCE_WORKERS is 2. Try changing it to 4. Specify the PARALLEL option with a value of 4, and set the VERBOSE flag to print more information when the command runs. Up to 4 workers will be started.

sql/set_max_parallel_maintenance_workers.sql
```
SET MAX_PARALLEL_MAINTENANCE_WORKERS=4;

VACUUM (PARALLEL 4, VERBOSE) users;
```

Let's explore Bloat in greater depth.

Simulating Bloat and Understanding Impact

As you saw earlier, Bloat refers to the amount of dead tuples that are present in your system. Dead tuples consume space that could be made available for live tuples. When bloat is very high it can contribute to worse performance.

9. https://paquier.xyz/postgresql-2/postgres-12-vacuum-skip-locked/
10. https://www.highgo.ca/2020/02/28/parallel-vacuum-in-upcoming-postgresql-13/