With that in mind, you're ready to add pg_cron. Add pg_cron to the extensions list in shared_preload_libraries in your PostgreSQL config file. The extension version will need to be compatible with your version of PostgreSQL.

Configure pg_cron to use the postgres database in the config file. In shared_preload_libraries, add cron.database_name = 'postgres' to do that.

To schedule a job, the cron.schedule function is provided from the extension. This function schedules jobs only in the database where pg_cron is configured. At this writing, pg_cron can be configured in only one database. Instead of that function, use the function cron.schedule_in_database to work around that limitation. This function is more complex but allows scheduling of jobs in other databases besides where pg_cron runs. You'll want to use this other function so that you can schedule jobs for the Rideshare database.

For a very high UPDATE rate table, you've decided to schedule a periodic manual VACUUM. This way VACUUM will run more frequently compared with relying solely on Autovacuum. Note that you can adjust Autovacuum settings per table and that's a good place to start. For this example, assume that you've done that already and you'd still like to run a manual Vacuum.

To schedule VACUUM for trips in the rideshare_development database for 10:00 UTC, run this statement from psql:

```
SELECT cron.schedule_in_database(
  job_name:='rideshare trips vacuum',
  schedule:='0 10 * * *',
  command:='VACUUM ANALYZE trips',
  database:='rideshare_development',
  username:='postgres'
);
```

You've now scheduled a job from the postgres database where pg_cron is running, to run for a table in the rideshare_development database, from the postgres database.

To view the job that was just scheduled, run this query from psql:

```
SELECT * FROM cron.job ORDER BY jobid;
```

Since it's scheduled but has not yet run, there will be no results from this query.

To break down the parts, cron is the schema where the function is defined, job is the table, and this table is in the postgres database.

Besides creating jobs, jobs can be altered like tables. To alter a scheduled job, use the cron.alter_job function.