Now that you've created a scheduled job, you'll want to monitor it. Read on to find out how to do that.

Monitoring pg_cron Scheduled Jobs

To see past runs of scheduled jobs, run this query from psql:

```
SELECT * from cron.job_run_details;
```

Jobs can be altered. Alter the job schedule to make it run every minute. After running it every minute, there should now be past run details to view in cron.job_run_details.

Run the following query to find the jobid for the *Rideshare trips vacuum* named job scheduled earlier in this section.

```
SELECT jobid, jobname, schedule, command FROM cron.job ORDER BY jobid;
```

If jobid is 1, run the following statement to modify the schedule attribute for jobid 1, setting the cron expression to mean "every 1 minute."

```
SELECT cron.alter_job(job_id:=1,schedule:='* * * * *');
```

Once this is set, you should see log entries like these:

```
2022-12-28 14:33:00.003 CST [91464] LOG:  \
cron job 1 starting: VACUUM ANALYZE trips
2022-12-28 14:33:00.049 CST [91464] LOG:  \
cron job 1 COMMAND completed: VACUUM
```

Run the query SELECT * from cron.job_run_details from psql again in the postgres database to confirm that the status of those runs shows as succeeded.

To verify this further, you should see that PostgreSQL has tracked that the trips table has been Vacuumed.

Check timestamps for the last manual ANALYZE and VACUUM on trips by running this query:

```
SELECT schemaname, relname, last_analyze, last_vacuum
FROM pg_stat_all_tables
WHERE relname = 'trips';
```

You've now configured a VACUUM ANALYZE job to run as a cron job on a schedule.

What if you were able to monitor pg_cron Scheduled Jobs via PgHero?