Installing the Rideshare Application

To install Rideshare, work from your terminal and use git to clone the application source code. Run git --version to confirm you're running at least version 2.

1. Download the application source code by typing cd to navigate to your project source code directory. For example, that might be cd ~/Projects. From there, run git clone https://github.com/andyatkinson/rideshare.git

2. Once cloned, change into the Rideshare by typing cd rideshare

   If you type pwd you should now be located in a directory like /Users/andy/Projects/rideshare.

3. From there, you're ready to install the Rideshare gems.

   Type ruby -v and confirm the version matches the version in .ruby-version, which was 3.2 at publication time. Install the bundler gem by typing gem install bundler. This is the one gem you'll install using gem install. Type bundler --version to confirm version 2 or greater is installed.

   With bundler installed, you're ready to use it to install the Rideshare gems. From the directory, type bundle install. This command installs Rails and all the gems needed to run the application.

   If you run into errors, please open an Issue on the project. A common error occurs when installing gems like pg that have native code dependencies, and the native code is not accessible. If you run into issues installing the pg gem, see the Appendix for more information.

4. If all gems were installed successfully, you're ready to set up the database. From your terminal:

   Use bin/rails db:create to create the development and test databases. The PostgreSQL server must be running. Using this technique will create a database role (user) named the same as your Mac OS user.

5. You now have the development database rideshare_development installed locally and ready to use.

   Installation is now complete. To further verify your installation, you may run bin/rails db:migrate and confirm no pending migrations exist. You may also wish to run the test suite for Rideshare for additional verifications.

6. To run the test suite for Rideshare, run bin/rails test in the Rideshare directory from your terminal.