In the SQL query `SELECT * FROM trips WHERE id = 1;` the fragment `WHERE id = 1` might be called the *where clause*.

To help identify SQL keywords, when the SQL statements operate on tables and fields, the tables and fields are lowercased.

In the example above, `trips` is a table name and `id` is a field name so they are lowercased.

SQL queries are meant to run in a SQL client. In this book psql is the recommended client, but any SQL client will work.

Once you're connected to PostgreSQL, copy and paste or type the SQL query into your client to run it.

Rails code is written in the Ruby programming language. Rails code will have `rails` in the code sample. Ruby is a interpreted language so you can run any Ruby code from the `bin/rails console` or the Ruby interpreter at any time. The `bin/rails console` is where you can run Active Record code and other Rails application code to see how it behaves. Copy and paste the code and or type it in and press Return to run it.

Note that both SQL and Ruby code can be run from the command line as well.

For SQL queries, psql supports a `--command` option. For example, type ‘ psql –command “select 1”‘ to run a SQL query from your terminal.

In Ruby you can run `ruby -e "puts 'hello'"` to run Ruby code from the command line. Rails extends this with `bin/rails runner` which allows you to run Rails code from the command line. From the Rideshare root directory for example, try this out by running `bin/rails runner "ActiveRecord::Base.connection.execute('select 1')"`. This command doesn't depend on you yet having the Rideshare data loaded, and is meant just to show that Active Record is connected to PostgreSQL and can execute a simple query.

Ruby and Rails methods will be lowercased and have explicit parentheses around them like `.average()`.

Database functions will be capitalized and have parentheses as well, like `SELECT AVG()` to help show that they are functions.

Ruby on Rails Frameworks with multiple words a space separated, for example “Active Record” or “Action Pack”.