shows conflicting lock modes on the Explicit Locking Documentation[9]. You will learn to map the SQL statements you send to the lock types they require in future chapters.

Although lock durations are typically very short, for high volume queries there can still be blocked queries or even *Deadlocks*. Deadlocks happen when two processes block each other permanently.[10]

For live information about locking activity, from psql query the pg_locks system catalog view as follows.

sql/view_pg_locks.sql
```
SELECT * FROM pg_locks;
```

That concludes the extremely brief introduction to lock activity. To recap, pg_stat_activity and pg_locks are system catalogs that can be queried to view live activity. As we move forward, you'll learn various ways to use this information. Lock durations are typically very short. Sometimes you'll need to simulate behaviors that you wish to monitor, like slow queries or long running locks. To do that, you'll create various experiments.

You're ready now to get started on setting up experiments.

Generating Fake Data For Experiments

You've installed and configured the Rideshare application and connected it to a database.

Did you know that on your database server instance, you can have multiple databases running? By default PostgreSQL actually installs several databases. In a default installation, you'll have databases called postgres, template0, and template1. You've created databases called rideshare_development and rideshare_test on your instance.

To verify all of these are there, run psql and type the \l meta-command to *list* the databases.

Type \c postgres to *connect* to the postgres database.

You may have thought "the database" was your PostgreSQL installation, but a database is really something that exists on your PostgreSQL server or instance. Each server has one or more databases.

9. https://www.postgresql.org/docs/current/explicit-locking.html
10. https://www.postgresql.org/docs/current/explicit-locking.html#LOCKING-DEADLOCKS