```
  --no-owner \
  --no-privileges \
  --file tmp/rideshare_database_dump.sql

# compress the file, force overwrite
gzip -f tmp/rideshare_database_dump.sql
```

Once the dump file was created it was uploaded to GitHub.

The amount of records was chosen to create a dump file that was large enough to be "interesting", but small enough to download quickly. For performance testing it helps to have large amounts of row data to work with, so after downloading the dump you may wish to generate even more data for your local Rideshare database.

Dumping the Database Schema

You may have been using pg_dump and not realized it. As the database schema is modified, changes show up as diffs to one of two possible files in your Rails application. The file is called db/schema.rb, when the Ruby format is used. Or the file is db/structure.sql, when the SQL format is used. Rideshare uses the SQL format. The SQL format uses pg_dump behind the scenes, but dumps only schema changes and not data. Explore pg_dump options to learn how to dump both schema and data.

In this section you'll download and load the data file. The steps are all written out in a shell script.

You downloaded and installed Rideshare already. cd into the source code rideshare directory.

From the Rideshare directory, run sh reset_and_load_data_dump.sh. If you prefer to run the commands one by one, that's ok too.

sh/reset_and_load_data_dump.sh

```
#!/bin/bash

# Important Note:
# Run this script from parent directory
#
# cd ..
# sh scripts/reset_and_load_data_dump.sh

echo "Make tmp dir"
mkdir -p tmp

echo "Download dump file"
curl -L \
https://github.com/andyatkinson/rideshare\
/raw/master/rideshare_database_dump.sql.gz \
  -o tmp/rideshare_database_dump.sql.gz
```