```
echo "Decompress file"
gzip -d tmp/rideshare_database_dump.sql.gz

echo "Decompressed file is around 100 MB"
du -h tmp/rideshare_database_dump.sql

echo "Re-create the empty database"
bin/rails db:drop:all
bin/rails db:create

echo "Load the dump file using psql. \
This will take a minute..."
psql --set ON_ERROR_STOP=on --quiet \
  --no-psqlrc \
  --output /dev/null \
  rideshare_development \
  --file tmp/rideshare_database_dump.sql

echo
echo "done!"
```

After the script runs, the rideshare_development database should be populated with one million records for the users table. The Rideshare users table is a polymorphic table and stores Drivers and Riders.

Run psql --dbname rideshare_development and count the users table records to verify that everything was loaded.

```
SELECT count(*) FROM users;
```

Describe the users table by running \d users from psql. Notice users has fields like first_name and email. The values in these fields are unique to individuals are considered sensitive. These are some of the columns you'll scrub!

How Do I Identify Sensitive Data?

To identify sensitive data, you'll look through all columns in all tables, identifying column names that describe personal information, and collect some sample rows. At most businesses, you'd then work with stakeholders like Product Owners, Business Analysts, and Security team members, to help classify the sensitivity of the data, and implement access controls.

Your rideshare_development database now has data that simulates a production database that is not scrubbed. This will be your starting point for developing your scrubbing process. If you wish to start over at any point, recreate the database (bin/rails db:reset) and download or load the dump file.