Use the CONCAT() function to assemble the string parts, crafting a full replacement email address from three parts.

In the function implementation below, everything is brought together to replace an email address. You can overwrite the earlier version that didn't have a body by copying and pasting this function into psql. If you wish to manage the function with Rideshare you may need to drop the function from psql and then bin/rails db:reset in Rideshare to restore the versions of the functions there.

sql/scrub_email_function_full.sql

```
-- replace email_address with random text that is the same
-- length as the unique portion of an email address
-- before the "@" symbol.
-- Make the minimum length 5 characters to avoid
-- MD5 text generation collisions
CREATE OR REPLACE FUNCTION scrub_email(
  email_address varchar(255)
) RETURNS varchar(255) AS $$
SELECT
CONCAT(
  SUBSTR(
    MD5(RANDOM()::text),
    0,
    GREATEST(
      LENGTH(
        SPLIT_PART(email_address, '@', 1)
      ) + 1, 6
    )
  ),
  '@',
  SPLIT_PART(email_address, '@', 2)
);
$$ LANGUAGE SQL;
```

Now that the function is defined, call it from a SELECT SQL statement as you did earlier from psql.

sql/scrub_email_short.sql

```
SELECT scrub_email('bob@gmail.com');
--     scrub_email
-- -------------------
--  5e9dd@gmail.com
```

You now have a mechanism to replace the sensitive parts of email addresses with scrubbed replacement text.

Try another email address that's longer and make sure the replacement text has the same length.

Run this SQL statement from psql.