sql/scrub_email_long.sql
```
SELECT scrub_email('bob-and-jane@gmail.com');
--       scrub_email
-- ------------------------
--  39246b1ccf0a@gmail.com
```

With your scrubber function in place, the next phase in the development of your scrubber solution is performing the scrubbing across all the rows.

How might you go about that?

Understanding Table Copying Trade-Offs

From this section forward, you'll focus on scrubbing table rows using the scrubber functions you've developed, and the two scrubbing techniques called Direct Updates and Table Copying.

First let's focus on the Table Copying technique. With Table Copying, the first step is to create a new destination (or "target") table that is a clone of the original (or "source") table. The destination table will have no data rows.

Run `psql --dbname rideshare_development` to connect to the `rideshare_development` database. Run the following command to copy the `users` table structure to a new table `users_copy`.

To do that you'll run the following SQL DDL statement from psql. This uses the `CREATE TABLE ... LIKE` table creation form. Run this statement:

sql/table_copying_create_like.sql
```
CREATE TABLE users_copy (LIKE users INCLUDING ALL);
```

You'll now have a `users_copy` table that's a clone of the original `users` table with no data rows. Explore it with `\d users_copy`. Confirm that there are no rows by running `SELECT COUNT(*) FROM users_copy;`.

The reason you didn't fill the table rows yet is very important and you'll find out why very soon.

You'll want to run these actions in Rideshare and you'll need data. If you have a messy database or want to start over, run the following commands from Rideshare to go back to a clean slate and with a significant volume of data.

To populate data you can either download the data dump as described in Chapter 1, or from an empty database you can use the built-in data generators Rake tasks in Rideshare. The example below resets the database to the original schema and uses the data generator tasks to load data.

```
bin/rails db:reset
```