ruby/migration_snippet_vehicle_enum_usage.rb

```
create_enum :vehicle_status, [
  VehicleStatus::DRAFT,
  VehicleStatus::PUBLISHED
]

add_column :vehicles, :status, :enum,
  enum_type: :vehicle_status,
  default: VehicleStatus::DRAFT,
  null: false
```

After migrating, you've now created new database objects. These objects will be dumped into the db/structure.sql file. You'll see a CREATE TYPE statement that looks like this:

sql/create_type_as_enum.sql

```
CREATE TYPE vehicle_status AS ENUM (
  'draft',
  'published'
);
```

The pg_type system catalog may be queried to list Enums. Query it as follows, confirming the enum name and values match the Migration above. This query should be run from psql.

sql/view_pg_types.sql

```
SELECT
  n.nspname AS enum_schema,
  t.typname AS enum_name,
  e.enumlabel AS enum_value
FROM pg_type t
JOIN pg_enum e ON t.oid = e.enumtypid
JOIN pg_catalog.pg_namespace n ON n.oid = t.typnamespace;

--  enum_schema |   enum_name    | enum_value
-- -------------+----------------+------------
--  public      | vehicle_status | published
--  public      | vehicle_status | draft
```

At this point, there is a compatibility problem between the database enumerated type and the Active Record model code. Update the model code to include the enum information.

ruby/active_record_enum_usage.rb

```
enum status: {
   draft: "draft",
   published: "published"
 }, _prefix: true
```