```
        android:layout_width="match_parent"
        android:layout_height="match_parent">

»       <androidx.fragment.app.FragmentContainerView
            android:id="@+id/hikes_nav_host"
            android:name="dev.hotwire.navigation.navigator.NavigatorHost"
            android:layout_width="match_parent"
            android:layout_height="0dp"
            app:defaultNavHost="false"
            app:layout_constraintBottom_toTopOf="@id/bottom_nav"
            app:layout_constraintTop_toTopOf="parent" />

        <androidx.fragment.app.FragmentContainerView
            android:id="@+id/hikers_nav_host"
            android:name="dev.hotwire.navigation.navigator.NavigatorHost"
            android:layout_width="match_parent"
            android:layout_height="0dp"
            app:defaultNavHost="false"
            app:layout_constraintBottom_toTopOf="@id/bottom_nav"
            app:layout_constraintTop_toTopOf="parent" />

        <!-- ... -->
    </androidx.constraintlayout.widget.ConstraintLayout>
```

You’re all done with XML for now. Back to Kotlin.

Manage Tabs with a Model

Like on iOS, we’ll use a model to represent each tab in the app. Start by creating a new package named `com.masilotti.hikingjournal.models` to hold your models.

Right-click the new package, select New, and then select Kotlin Class/File.