```
        configuration = NavigatorConfiguration(
            name = "hikes",
            navigatorHostId = R.id.hikes_nav_host,
            startLocation = "$baseURL/hikes"
        )
    )

    private val hikers = HotwireBottomTab(
        title = "Hikers",
        iconResId = android.R.drawable.ic_menu_myplaces,
        configuration = NavigatorConfiguration(
            name = "hikers",
            navigatorHostId = R.id.hikers_nav_host,
            startLocation = "$baseURL/users"
        )
    )
```

These icons, prefaced with `android.R.drawable`, come from Android's built-in (but limited) asset library.[27]

Next, expose these new tabs in a list at the bottom of the file. We'll use this variable to configure the tabs back in `MainActivity`.

ch04_13/android/app/src/main/java/com/masilotti/hikingjournal/models/Tabs.kt

```
    package com.masilotti.hikingjournal.activities.models

    import com.masilotti.hikingjournal.R
    import com.masilotti.hikingjournal.activities.baseURL
    import dev.hotwire.navigation.navigator.NavigatorConfiguration
    import dev.hotwire.navigation.tabs.HotwireBottomTab

    private val hikes = HotwireBottomTab(
        // ...
    )

    private val hikers = HotwireBottomTab(
        // ...
    )

»   val mainTabs = listOf(
»       hikes,
```