Initialize the Tab Bar

Open `MainActivity` and create a private `HotwireBottomNavigationController` property. Declare it with `lateinit` so it can be created *after* the fragment is initialized.

ch04_14/android/app/src/main/java/com/masilotti/hikingjournal/activities/MainActivity.kt

```
// ...
import dev.hotwire.core.turbo.config.PathConfiguration
import dev.hotwire.navigation.activities.HotwireActivity
import dev.hotwire.navigation.navigator.NavigatorConfiguration
» import dev.hotwire.navigation.tabs.HotwireBottomNavigationController
import dev.hotwire.navigation.util.applyDefaultImeWindowInsets

const val baseURL = "http://10.0.2.2:3000"

class MainActivity : HotwireActivity() {
»     private lateinit var bottomNavigationController:
»             HotwireBottomNavigationController

    override fun onCreate(savedInstanceState: Bundle?) {
        // ...
    }

    override fun navigatorConfigurations() = listOf(
        // ..
    )
}
```

Then, create a new private function at the bottom of `MainActivity` that initializes `HotwireBottomNavigationController` with a reference to our bottom navigation view. Call this function at the bottom of `onCreate(savedInstanceState: Bundle?)`.

ch04_15/android/app/src/main/java/com/masilotti/hikingjournal/activities/MainActivity.kt

```
package com.masilotti.hikingjournal.activities
```