ch06_02/android/app/src/main/AndroidManifest.xml

```
<manifest xmlns:android="http://schemas.android.com/apk/res/android"
    xmlns:tools="http://schemas.android.com/tools">

    <uses-permission android:name="android.permission.INTERNET" />

    <application
»       android:name=".HikingJournalApplication"
        android:allowBackup="true"
        android:dataExtractionRules="@xml/data_extraction_rules"
        android:fullBackupContent="@xml/backup_rules"
        android:icon="@mipmap/ic_launcher"
        android:label="@string/app_name"
        android:roundIcon="@mipmap/ic_launcher_round"
        android:supportsRtl="true"
        android:theme="@style/Theme.HikingJournal"
        android:usesCleartextTraffic="true"
        tools:targetApi="31">

        <!-- ... -->
    </application>

</manifest>
```

Now, we can move the Hotwire Native code that loads our path configuration from MainActivity to the Application subclass.

ch06_02/android/app/src/main/java/com/masilotti/hikingjournal/HikingJournalApplication.kt

```
package com.masilotti.hikingjournal

import android.app.Application
» import com.masilotti.hikingjournal.activities.baseURL
» import dev.hotwire.core.config.Hotwire
» import dev.hotwire.core.turbo.config.PathConfiguration

class HikingJournalApplication : Application() {
    override fun onCreate() {
        super.onCreate()

»       Hotwire.loadPathConfiguration(
```