```
<androidx.constraintlayout.widget.ConstraintLayout
    xmlns:android="http://schemas.android.com/apk/res/android"
    xmlns:app="http://schemas.android.com/apk/res-auto"
    android:layout_width="match_parent"
    android:layout_height="match_parent">

    <androidx.compose.ui.platform.ComposeView
        android:id="@+id/compose_view"
        android:layout_width="match_parent"
        android:layout_height="match_parent" />

</androidx.constraintlayout.widget.ConstraintLayout>
```

In the newly created `MapFragment.kt`, replace the contents with an empty subclass of a `HotwireFragment`. This subclass wires us up to Hotwire Native, exposing a `Navigator` instance, which we'll use later in the chapter.

ch06_09/android/app/src/main/java/com/masilotti/hikingjournal/fragments/MapFragment.kt

```
package com.masilotti.hikingjournal.fragments

import dev.hotwire.navigation.fragments.HotwireFragment

class MapFragment : HotwireFragment() {
}
```

Override `onCreateView()` in the fragment to render our custom `ComposeView` by inflating it via `R`. Remember, `R` exposes our project's non-code resources.

ch06_10/android/app/src/main/java/com/masilotti/hikingjournal/fragments/MapFragment.kt

```
package com.masilotti.hikingjournal.fragments

» import android.os.Bundle
» import android.view.LayoutInflater
» import android.view.View
» import android.view.ViewGroup
» import com.masilotti.hikingjournal.R
import dev.hotwire.navigation.fragments.HotwireFragment
```