```
    class MapFragment : HotwireFragment() {
»       override fun onCreateView(
»           inflater: LayoutInflater,
»           container: ViewGroup?,
»           savedInstanceState: Bundle?
»       ): View {
»           val view = inflater.inflate(R.layout.fragment_map, container, false)
»           return view
»       }
    }
```

Then, find the `ComposeView` in `view` and apply `setContent()`, bridging the gap to Compose. Inside, render a `Text()` node with the traditional "Hello, World!" string.

ch06_11/android/app/src/main/java/com/masilotti/hikingjournal/fragments/MapFragment.kt

```
    // ...
    import android.view.ViewGroup
»   import androidx.compose.material3.Text
»   import androidx.compose.ui.platform.ComposeView
    import com.masilotti.hikingjournal.R
    import dev.hotwire.navigation.fragments.HotwireFragment

    class MapFragment : HotwireFragment() {
        override fun onCreateView(
            inflater: LayoutInflater,
            container: ViewGroup?,
            savedInstanceState: Bundle?
        ): View {
            val view = inflater.inflate(R.layout.fragment_map, container, false)
»           view.findViewById<ComposeView>(R.id.compose_view).apply {
»               setContent {
»                   Text(text = "Hello, World!")
»               }
»           }
            return view
        }
    }
```