```
        GoogleMap(cameraPositionState = cameraPositionState) {
»           Marker(
»               state = markerState,
»               title = "Mount Tabor"
»           )
        }
    }
```

Finally, replicate our design on iOS by using a hybrid map type.

ch06_19/android/app/src/main/java/com/masilotti/hikingjournal/fragments/MapFragment.kt

```
    // ...
    import com.google.maps.android.compose.GoogleMap
»   import com.google.maps.android.compose.MapProperties
»   import com.google.maps.android.compose.MapType
    import com.google.maps.android.compose.Marker
    // ...

    @HotwireDestinationDeepLink(uri = "hotwire://fragment/map")
    class MapFragment : HotwireFragment() {
        // ...
    }

    @Composable
    fun MapView() {
        val coordinate = LatLng(45.511881, -122.595706)
        val markerState = rememberMarkerState(position = coordinate)
        val cameraPositionState = rememberCameraPositionState {
            position = CameraPosition.fromLatLngZoom(coordinate, 15f)
        }
»       GoogleMap(
»           cameraPositionState = cameraPositionState,
»           properties = MapProperties(mapType = MapType.HYBRID)
»       ) {
            Marker(
                state = markerState,
                title = "Mount Tabor"
            )
        }
    }
```