```
    }
```

To initiate the network request, add an empty function named `fetchCoordinates()`. Fetching data from the server will happen asynchronously, so add the `suspend` keyword to "wait" for this execution to finish when called.

ch06_24/android/app/src/main/java/com/masilotti/hikingjournal/viewmodels/HikeViewModel.kt

```
package com.masilotti.hikingjournal.viewmodels

import androidx.compose.runtime.mutableStateOf
import androidx.lifecycle.ViewModel
import com.masilotti.hikingjournal.models.Hike

class HikeViewModel(private val url: String) : ViewModel() {
    var hike = mutableStateOf<Hike?>(null)
        private set

»   suspend fun fetchCoordinates() {
»   }
}
```

Implement the function by reading text from the initialized `url`. Parse the response to create a new `Hike` instance and assign it to the `hike` property's `value`.

ch06_25/android/app/src/main/java/com/masilotti/hikingjournal/viewmodels/HikeViewModel.kt

```
package com.masilotti.hikingjournal.viewmodels

import androidx.compose.runtime.mutableStateOf
import androidx.lifecycle.ViewModel
import com.masilotti.hikingjournal.models.Hike
» import kotlinx.coroutines.Dispatchers
» import kotlinx.coroutines.withContext
» import org.json.JSONObject
» import java.net.URL
```