OK, view model done. Connect it to the fragment by adding a mutable property to `MapFragment.kt`.

ch06_27/android/app/src/main/java/com/masilotti/hikingjournal/fragments/MapFragment.kt

```
    // ...
    import com.google.maps.android.compose.rememberMarkerState
    import com.masilotti.hikingjournal.R
»   import com.masilotti.hikingjournal.viewmodels.HikeViewModel
    import dev.hotwire.navigation.destinations.HotwireDestinationDeepLink
    import dev.hotwire.navigation.fragments.HotwireFragment

    @HotwireDestinationDeepLink(uri = "hotwire://fragment/map")
    class MapFragment : HotwireFragment() {
»       private lateinit var viewModel: HikeViewModel

        override fun onCreateView(
            inflater: LayoutInflater,
            container: ViewGroup?,
            savedInstanceState: Bundle?
        ): View {
»           viewModel = HikeViewModel(url = "${navigator.location}.json")

            val view = inflater.inflate(R.layout.fragment_map, container, false)
            view.findViewById<ComposeView>(R.id.compose_view).apply {
                setContent {
                    MapView()
                }
            }
            return view
        }
    }

    // ...
```

This fragment subclasses `HotwireFragment`, which grants us access to a `Navigator` instance. `Navigator.location` provides the most recently visited URL string, which we append the JSON extension to and pass to the view model. `lateinit` defers initialization of the view model until we have the URL string ready.