```
@HotwireDestinationDeepLink(uri = "hotwire://fragment/map")
class MapFragment : HotwireFragment() {
    // ...
}

@Composable
fun MapView(viewModel: HikeViewModel) {
    val hike = viewModel.hike.value
    if (hike != null) {
        val markerState = rememberMarkerState(position = hike.coordinate)
        val cameraPositionState = rememberCameraPositionState {
            position = CameraPosition.fromLatLngZoom(hike.coordinate, 15f)
        }
        GoogleMap(
            cameraPositionState = cameraPositionState,
            properties = MapProperties(mapType = MapType.HYBRID)
        ) {
            Marker(
                state = markerState,
                title = hike.name
            )
        }
    }
}
```

Before you run the app, do you know what will happen? I'll give you a hint: We ran into the exact same problem on iOS. That's right—we never told our view model to fetch the data from the server!

Call `fetchCoordinates()` on the view model, and then wrap it in a `LaunchedEffect`. This ensures any changes to the underlying `mutableStateOf<Hike?>()` bubble up to the fragment and re-render the `@Composable`.

ch06_30/android/app/src/main/java/com/masilotti/hikingjournal/fragments/MapFragment.kt

```
// ...
import androidx.compose.runtime.Composable
import androidx.compose.runtime.LaunchedEffect
import androidx.compose.ui.platform.ComposeView
```