Create a Native Component

Get started by opening Android Studio and creating a new package under `com.masilotti.hikingjournal` and name it `components`. Inside that package, create a new Kotlin file and name it `ButtonComponent`.

Inside this file, declare a `BridgeComponent` subclass named `ButtonComponent`.

ch08_01/android/app/src/main/java/com/masilotti/hikingjournal/components/ButtonComponent.kt

```
package com.masilotti.hikingjournal.components

import dev.hotwire.core.bridge.BridgeComponent
import dev.hotwire.core.bridge.BridgeDelegate
import dev.hotwire.navigation.destinations.HotwireDestination

class ButtonComponent(
    name: String,
    private val bridgeDelegate: BridgeDelegate<HotwireDestination>
) : BridgeComponent<HotwireDestination>(name, bridgeDelegate) {
}
```

Excluding the package and import statements, these five lines of code can be pretty intimidating. Coming from Ruby, I had no idea what was going on the first time I saw them! Let's break it down.

`ButtonComponent` inherits from `BridgeComponent`, signified by the colon. This isn't any different than what you did when you made `MapFragment` inherit from `HotwireFragment` in Chapter 6, *Render Native Screens with Jetpack Compose*.

```
class MapFragment : HotwireFragment() {
  // ...
}
```