ch08_02/android/app/src/main/java/com/masilotti/hikingjournal/components/ButtonComponent.kt

```
package com.masilotti.hikingjournal.components

import dev.hotwire.core.bridge.BridgeComponent
import dev.hotwire.core.bridge.BridgeDelegate
» import dev.hotwire.core.bridge.Message
import dev.hotwire.navigation.destinations.HotwireDestination

class ButtonComponent(
    name: String,
    private val bridgeDelegate: BridgeDelegate<HotwireDestination>
) : BridgeComponent<HotwireDestination>(name, bridgeDelegate) {
»     override fun onReceive(message: Message) {
»         TODO("Not yet implemented")
»     }
}
```

Next, you need to make Hotwire Native aware of the component. You won't instantiate bridge components directly; Hotwire Native will do it for us. Open `HikingJournalApplication` and register `ButtonComponent` with the name "button", which aligns it with the value of `component` on the JavaScript side of things.

ch08_03/android/app/src/main/java/com/masilotti/hikingjournal/HikingJournalApplication.kt

```
package com.masilotti.hikingjournal

import android.app.Application
import com.masilotti.hikingjournal.activities.baseURL
» import com.masilotti.hikingjournal.components.ButtonComponent
import com.masilotti.hikingjournal.fragments.MapFragment
» import dev.hotwire.core.bridge.BridgeComponentFactory
import dev.hotwire.core.config.Hotwire
import dev.hotwire.core.turbo.config.PathConfiguration
» import dev.hotwire.navigation.config.registerBridgeComponents
import dev.hotwire.navigation.config.registerFragmentDestinations
import dev.hotwire.navigation.fragments.HotwireWebFragment

class HikingJournalApplication : Application() {
```