Bug: fixed. Let's refactor a bit. When I build Compose views, I like to keep them self-contained as much as possible. So let's extract the button code to a `@Composable` function, as you did in *Build a Compose View*. Pass in the button title so you can easily make it dynamic later.

ch08_13/android/app/src/main/java/com/masilotti/hikingjournal/components/ButtonComponent.kt

```
  // ...
  import androidx.compose.material3.Button
  import androidx.compose.material3.Text
» import androidx.compose.runtime.Composable
  import androidx.compose.ui.platform.ComposeView
  import dev.hotwire.core.bridge.BridgeComponent
  // ...

  class ButtonComponent(
      name: String,
      private val bridgeDelegate: BridgeDelegate<HotwireDestination>
  ) : BridgeComponent<HotwireDestination>(name, bridgeDelegate) {
      // ...

      private fun addButton(message: Message) {
          val composeView = ComposeView(fragment.requireContext()).apply {
              id = buttonId
              setContent {
»                 ToolbarButton(
»                     title = "Sign in",
»                     onClick = { replyTo(message.event) }
»                 )
              }
          }
          // ...
      }

      // ...
  }

» @Composable
» private fun ToolbarButton(title: String, onClick: () -> Unit) {
»     Button(
»         onClick = onClick
```