```
»       head :created
      end

      private

      def notification_token
        params.require(:notification_token).permit(:token, :platform)
      end
    end
```

Devices can now POST to `/notification_tokens` to register their tokens with the Rails server. Up next, let's learn how to send a notification when someone likes a hike.

Send Push Notifications with Noticed

To send a notification to an iOS device, you need to send an authenticated HTTP request to Apple Push Notification service (APNs). Instead of doing this manually, I like to use the Noticed gem[77] to abstract away the annoying parts. Noticed will also help keep your code organized with a `Notifier` subclass—here, you could configure different types of notifications like SMS, Email, Discord, and more.

Start by adding the Noticed and Apnotic[78] gems by switching to the `rails` directory and executing `bundle add noticed apnotic`. Noticed uses Apnotic under the hood to authorize and manage network connections to APNs.

Install the Noticed migrations by running `bin/rails noticed:install:migrations` and migrating the database with `bin/rails db:migrate`.

Notifications are sent via `Notifier` subclasses from Noticed. Create a new one by running `bin/rails generate noticed:notifier NewLikeNotifier`. This will create `NewLikeNotifier` and `ApplicationNotifier` under `app/notifiers`. Use `ApplicationNotifier` to store generic or reusable logic for your notifiers, like `ApplicationController` does for your controllers.