Here, you're setting `alert` to display a message to the user to let them know someone liked their hike. Check out the Apnotic documentation[80] for all the options you can use for notifications.

One of those options is `custom_payload`. This is a special option reserved for application-specific, custom logic. Use this to include the path of the hike. When the user opens the notification, you can use this option to build a URL and deep link to the hike's page.

ch10_18/rails/app/notifiers/new_like_notifier.rb

```
  class NewLikeNotifier < ApplicationNotifier
»   required_param :hike

    deliver_by :ios do |config|
      config.device_tokens = -> {
        recipient.notification_tokens.where(platform: :iOS).pluck(:token)
      }

      config.format = ->(apn) {
        apn.alert = "Someone liked your hike!"
»       apn.custom_payload = {
»         path: hike_path(params[:hike])
»       }
      }
    end
  end
```

`required_param :hike` forces us to pass in an object with the `hike:` keyword when creating the notification, like so: `NewLikeNotifier.with(hike: Hike.first)`.

Along with the device token, you need to authenticate your Apple Developer account with APNs. Configure the four required attributes, reading each from Rails credentials. We'll come back and add these to your development credentials later.

ch10_19/rails/app/notifiers/new_like_notifier.rb

```
  class NewLikeNotifier < ApplicationNotifier
```