- `team_id`—all the way in the upper right on the same page
- `apns_key`—the downloaded .p8 file as plain-text

For the last field, use `|-` to collapse white space for a multiline string. This allows you to copy-paste the private key without worrying about formatting. Here's what my decrypted credentials file looks like for an old key:

```
ios:
  bundle_identifier: com.masilotti.HikingJournal
  key_id: C3P98234KT
  team_id: 6JS2VP4ATY
  apns_key: |-
    -----BEGIN PRIVATE KEY-----
    MIGTAgEAMBMGByqGSM49AgEGCCqGSM49AwEHBHkwdwIBAQQgZx5PD8rL5JqwMcKt
    pT9SXTkFmNlJ3oWmTG3DRKv5H2OgCgYIKoZIzj0DAQehRANCAAQw1eXZF7L+tx0h
    pKZy9fEdqYtBPsUq4kYHTgYKMfHv7NpytC0JXMGt29zDbHSiZnHtqiwvGTxE/WEj
    yVRgKXrs
    -----END PRIVATE KEY-----
```

Your Rails server is now set up to send push notifications to iOS devices. It can trigger the authorization dialog with the bridge component, persist the `NotificationToken` records to the database, and send notifications with `NewLikeNotifier`. Up next, we'll tackle the native iOS code before moving on to Android.