```
    let baseURL = URL(string: "http://localhost:3000")!

    class SceneDelegate {
»       var window: UIWindow?
    }
```

Unlike Ruby, variables in Swift must be explicitly typed. The question mark at the end of the `UIWindow` type makes this property optional. `window` needs to be optional because it's assigned after `SceneDelegate` is instantiated. But you won't ever assign anything to the window directly, iOS takes care of that when the app launches.

After the window, create a `Navigator` property. Part of Hotwire Native, this property abstracts the navigation between web screens and acts as our main interface to the framework. We configure it with an arbitrary `name`, "main". A unique `name` is required when using multiple `Navigator` instances, like when we get to multiple tabs in Chapter 4, *Add a Native Tab Bar*. `startLocation` is set to the page we want to load when the app is launched, `/hikes`.

ch01_05/ios/HikingJournal/SceneDelegate.swift

```
    import HotwireNative
    import UIKit

    let baseURL = URL(string: "http://localhost:3000")!

    class SceneDelegate {
        var window: UIWindow?

»       private let navigator = Navigator(configuration: .init(
»           name: "main",
»           startLocation: baseURL.appending(path: "hikes")
»       ))
    }
```

The navigator is an implementation detail of `SceneDelegate`. No one else needs to know about it, so we can make it private. It's also declared with `let`,