```
    /// its own `Navigator` instance.
    ///
    /// This controller loads tabs defined by `HotwireTab` and configures each
    /// one with its own `Navigator`. The currently selected tab's navigator
    /// is exposed via the `activeNavigator` property.
    open class HotwireTabBarController: UITabBarController, NavigationHandler {
        // ...
    }
```

Open SceneDelegate and create a private NotificationRouter, passing in the HotwireTabBarController as the navigationHandler parameter. Then, assign the global notification delegate to the NotificationRouter instance. This tells iOS that you want to handle incoming notifications with your custom router.

ch10_43/ios/App/Delegates/SceneDelegate.swift

```
    // ...

    class SceneDelegate: UIResponder, UIWindowSceneDelegate {
        var window: UIWindow?

        private lazy var tabBarController = HotwireTabBarController(
            navigatorDelegate: self
        )
»       private lazy var notificationRouter = NotificationRouter(
»           navigationHandler: tabBarController
»       )

        func scene(
            _ scene: UIScene,
            willConnectTo session: UISceneSession,
            options connectionOptions: UIScene.ConnectionOptions
        ) {
»           UNUserNotificationCenter.current().delegate = notificationRouter
            window?.rootViewController = tabBarController
            tabBarController.load(HotwireTab.all)
        }
    }

    // ...
```