```
        override fun onReceive(message: Message) {
            // Request notification permission.
        }
    }
```

*Unlike* on iOS, requesting runtime permissions[88] must be done when *initializing* a `Fragment`. It can't be done dynamically as we did on iOS. So, for Android, you need an additional step: a custom `HotwireWebFragment` extension (subclass) to add your permission request logic.

**Wait, What's a HotwireWebFragment?**



A `HotwireWebFragment` is the base class from which all "standard" web fragments (non-dialogs) in a Hotwire app should extend from.

Every time a web-powered screen is displayed, a `HotwireWebFragment` is used. This fragment, provided by Hotwire Native Android, handles everything related to the web view and the content it's rendering.

By extending (subclassing) this, we can add additional functionality or logic without having to worry about the details of the managed web view.

Create a new class in the `fragments` package and name it `WebFragment`. Reuse the same `@HotwireDestinationDeepLink` as `HotwireWebFragment` to ensure every web screen gets rendered with this fragment. Remember, we set this in our path configuration in code.

ch10_53/android/app/src/main/java/com/masilotti/hikingjournal/fragments/WebFragment.kt

```
package com.masilotti.hikingjournal.fragments

import dev.hotwire.navigation.destinations.HotwireDestinationDeepLink
```