```
import dev.hotwire.navigation.fragments.HotwireWebFragment

@HotwireDestinationDeepLink("hotwire://fragment/web")
class WebFragment : HotwireWebFragment() {
}
```

Add a private `requestPermissionLauncher` property that, when granted, calls `registerForTokenChanges()`. We'll launch this dynamically from the bridge component.

ch10_54/android/app/src/main/java/com/masilotti/hikingjournal/fragments/WebFragment.kt

```
package com.masilotti.hikingjournal.fragments

» import androidx.activity.result.contract.ActivityResultContracts
import dev.hotwire.navigation.destinations.HotwireDestinationDeepLink
import dev.hotwire.navigation.fragments.HotwireWebFragment

@HotwireDestinationDeepLink("hotwire://fragment/web")
class WebFragment : HotwireWebFragment() {
»     private val contract = ActivityResultContracts.RequestPermission()
»     private val requestPermissionLauncher =
»         registerForActivityResult(contract) { isGranted ->
»             if (isGranted) registerForTokenChanges()
»         }
»
»     private fun registerForTokenChanges() {
»     }
}
```

Inside of `registerForTokenChanges()`, add a completion handler to the Firebase token. Every time the value of the token changes, this code will be called. After we create the view model, we'll come back and replace the comment to make the network request.

ch10_55/android/app/src/main/java/com/masilotti/hikingjournal/fragments/WebFragment.kt

```
package com.masilotti.hikingjournal.fragments
```