```
        // ...

    »   fun requestNotificationPermission() {
    »       if (Build.VERSION.SDK_INT >= Build.VERSION_CODES.TIRAMISU) {
    »           val permission = Manifest.permission.POST_NOTIFICATIONS
    »           requestPermissionLauncher.launch(permission)
    »       }
    »   }

        private fun registerForTokenChanges() {
            // ...
        }
    }
```

Back in NotificationTokenComponent, cast the bridgeDelegate.destination as a WebFragment, our custom subclass, just as we did in the ButtonComponent code .

ch10_57/android/app/src/main/java/com/masilotti ... journal/components/NotificationTokenComponent.kt

```
    package com.masilotti.hikingjournal.components

  » import com.masilotti.hikingjournal.fragments.WebFragment
    import dev.hotwire.core.bridge.BridgeComponent
    import dev.hotwire.core.bridge.BridgeDelegate
    import dev.hotwire.core.bridge.Message
    import dev.hotwire.navigation.destinations.HotwireDestination

    class NotificationTokenComponent(
        name: String,
        private val bridgeDelegate: BridgeDelegate<HotwireDestination>
    ) : BridgeComponent<HotwireDestination>(name, bridgeDelegate) {
    »   private val fragment: WebFragment
    »       get() = bridgeDelegate.destination.fragment as WebFragment

        override fun onReceive(message: Message) {
    »       fragment.requestNotificationPermission()
        }
    }
```