Can you guess what's next? I'll give you a hint: we just created a new bridge component and a new fragment. That's right! We need to register these with Hotwire Native.

Open `HikingJournalApplication` and register them with the framework. While you're in there, make sure to initialize Firebase, too.

ch10_58/android/app/src/main/java/com/masilotti/hikingjournal/HikingJournalApplication.kt

```
  package com.masilotti.hikingjournal

  import android.app.Application
» import com.google.firebase.FirebaseApp
  import com.masilotti.hikingjournal.activities.baseURL
  import com.masilotti.hikingjournal.components.ButtonComponent
» import com.masilotti.hikingjournal.components.NotificationTokenComponent
  import com.masilotti.hikingjournal.fragments.MapFragment
» import com.masilotti.hikingjournal.fragments.WebFragment
  import dev.hotwire.core.bridge.BridgeComponentFactory
  import dev.hotwire.core.bridge.KotlinXJsonConverter
  import dev.hotwire.core.config.Hotwire
  // ...

  class HikingJournalApplication : Application() {
      override fun onCreate() {
          super.onCreate()

»         FirebaseApp.initializeApp(this)

          Hotwire.loadPathConfiguration(
              // ...
          )

          Hotwire.registerFragmentDestinations(
              MapFragment::class,
»             WebFragment::class,
          )

          Hotwire.registerBridgeComponents(
              BridgeComponentFactory("button", ::ButtonComponent),
»             BridgeComponentFactory(
```