Back in `onCreate(savedInstanceState: Bundle?)` after the call to `super`, set the content view with `R.layout.activity_main`. This finds the resource (“R”) in the `layout` directory named `activity_main.xml`. Android Studio automatically generates R for you on a successful build.

ch01_18/android/app/src/main/java/com/masilotti/hikingjournal/MainActivity.kt

```
package com.masilotti.hikingjournal

import android.os.Bundle
import dev.hotwire.navigation.activities.HotwireActivity

class MainActivity : HotwireActivity() {
    override fun onCreate(savedInstanceState: Bundle?) {
        super.onCreate(savedInstanceState)
»       setContentView(R.layout.activity_main)
    }
}
```

Before we move on, we need to address a recent change in Android.[19] Starting with Android SDK 35, apps are displayed edge-to-edge—the window fills the entire height of the display and renders behind the status bar at the top of the screen.

To make sure this doesn’t overlap our web content, we need to configure our layout to shrink behind the bars.

ch01_19/android/app/src/main/java/com/masilotti/hikingjournal/MainActivity.kt

```
package com.masilotti.hikingjournal

import android.os.Bundle
» import android.view.View
» import androidx.activity.enableEdgeToEdge
import dev.hotwire.navigation.activities.HotwireActivity
» import dev.hotwire.navigation.util.applyDefaultImeWindowInsets

class MainActivity : HotwireActivity() {
    override fun onCreate(savedInstanceState: Bundle?) {
        super.onCreate(savedInstanceState)
```