```
»     override fun navigatorConfigurations(): List<NavigatorConfiguration> {
»         TODO("Not yet implemented")
»     }
  }
```

The red squiggle and any errors are now gone, but we need to address the added TODO note. `navigatorConfigurations()` requires an array of `NavigatorConfiguration` instances, one for each web view you want to display. We won't need more than one of these until we get to multiple tabs in Chapter 4, *Add a Native Tab Bar*.

Each `NavigatorConfiguration` instance requires three parameters:

- `name`: A unique name to identify the underlying web view.
- `startLocation`: The URL, as a string, to visit upon launch.
- `navigatorHostId`: A reference to a `FragmentContainerView` from the layout XML.

Before implementing the configurations function, we'll mimic the global URL variable from the iOS app. Declare a variable named `baseURL` outside of `MainActivity` to ensure access across the codebase.

ch01_21/android/app/src/main/java/com/masilotti/hikingjournal/MainActivity.kt

```
  package com.masilotti.hikingjournal

  import android.os.Bundle
  import android.view.View
  import androidx.activity.enableEdgeToEdge
  import dev.hotwire.navigation.activities.HotwireActivity
  import dev.hotwire.navigation.navigator.NavigatorConfiguration
  import dev.hotwire.navigation.util.applyDefaultImeWindowInsets

» const val baseURL = "http://10.0.2.2:3000"

  class MainActivity : HotwireActivity() {
      // ...
  }
```