```
Failed examples:

rspec ./spec/integration/app/ledger_spec.rb:20 #                    ↩
ExpenseTracker::Ledger#record with a valid expense successfully saves the   ↩
expense in the DB
rspec ./spec/integration/app/ledger_spec.rb:34 #                    ↩
ExpenseTracker::Ledger#record when the expense lacks a payee rejects the    ↩
expense as invalid

Randomized with seed 32043
```

The numbers in square brackets are called *example IDs*; they indicate each example's position in its file, relative to other examples and nested groups. For example, some_spec.rb[2:3] would mean "the third example inside the second group in some_spec.rb." You can paste these values into your terminal just as you did with line numbers in *Running Specific Failures*, on page 21.

With this set of specs, we can see that the new spec causes the prior spec to fail if the new one runs first. Our database writes are leaking between tests.

Watch for Test Interaction in Integration Specs



Your integration specs interact with external resources: the file system, the database, the network, and so on. Because these resources are shared, you have to take extra care to restore the system to a clean slate after each spec.

Isolating Your Specs Using Database Transactions

To solve this issue, we're going to wrap each spec in a database transaction. After each example runs, we want RSpec to *roll back* the transaction, canceling any writes that happened and leaving the database in a clean state. Sequel provides a test-friendly method for wrapping code in transactions.[5]

An RSpec around hook would be perfect for this task. You already have a spec/support/db.rb file for database support code, so add it there, inside the RSpec.configure block:

06-integration-specs/07/expense_tracker/spec/support/db.rb

```
c.around(:example, :db) do |example|
  DB.transaction(rollback: :always) { example.run }
end
```

The sequence of calls in the new hook is a bit twisty, so bear with us for a second. For each example marked as requiring the database (via the :db tag; you'll see how to use this in a moment), the following events happen:

5. http://sequel.jeremyevans.net/rdoc/files/doc/testing_rdoc.html