```
spec/acceptance/expense_tracker_api_spec.rb:

Randomized with seed 24954

An error occurred in a `before(:suite)` hook.
Failure/Error: Sequel.extension :migration

NameError:
  uninitialized constant Sequel
# ./spec/support/db.rb:3:in `block (2 levels) in <top (required)>'

Finished in 0.01902 seconds (files took 0.16858 seconds to load)
0 examples, 0 failures, 1 error occurred outside of examples

Randomized with seed 24954
```

We need to find a better place to load config/sequel.rb. In general, it's a good idea to load dependencies right where they are used. In this case, ledger.rb has a direct dependency on your Sequel configuration. Let's load the config from the top of that file:

06-integration-specs/09/expense_tracker/app/ledger.rb

```
require_relative '../config/sequel'
```

With that line in place, you can remove the require_relative call from spec/integration/app/ledger_spec.rb. Now, each of your spec files will pass when you run it individually:

```
$ (for f in `find spec -iname '*_spec.rb'`; do
    echo "$f:"
    bundle exec rspec $f -fp || exit 1
  done)
spec/acceptance/expense_tracker_api_spec.rb:

Randomized with seed 64689
.

Finished in 0.02758 seconds (files took 0.20933 seconds to load)
1 example, 0 failures

Randomized with seed 64689

spec/integration/app/ledger_spec.rb:

Randomized with seed 7247
....

Finished in 0.01689 seconds (files took 0.15956 seconds to load)
4 examples, 0 failures

Randomized with seed 7247

spec/unit/app/api_spec.rb:

Randomized with seed 21495
........
```