More Validations

So far, the Ledger class only validates one property of incoming expenses: that they have a payee. What are some other things the record method should check before saving an expense? Write integration specs for these checks, and implement the behavior.

Data Format

The current version of the app assumes all input is JSON. You could post XML, and the code would still try to parse it as JSON:

```
$ curl --data 'some xml here' \
       --header "Content-Type: text/xml" \
       http://localhost:9292/expenses
```

For this exercise, you'll add the ability for the expense tracker to read and write XML in addition to JSON. First, you'd need to decide on an XML format. If you use something like the Ox library, you'll get a format, reader, and writer for free.[7]

The next thing to consider is how callers will select the data format. Luckily, HTTP provides a means to do this with headers, which many HTTP clients and servers already understand:[8]

- The expenses POST endpoint would look at the HTTP Content-Type header for the standard MIME types for these formats, application/json or text/xml, to know how to parse the incoming data.[9]
- The expenses/:date GET endpoint would read the Accept header, similar to Content-Type, and decide how to format the outbound data.

Along the way, you'll end up deciding what to do when the caller asks for an unsupported format, or when the incoming data doesn't match the format advertised. The unit specs for your routing layer are a good place to check for all these edge cases.

Rack::Test and Sinatra provide helper methods for you to read and write the various HTTP headers:

- In Rack::Test, call header to set up your request headers before calling get or post.[10]

7. http://www.ohler.com/ox/
8. https://en.wikipedia.org/wiki/Content_negotiation
9. https://en.wikipedia.org/wiki/MIME#Content-Type
10. http://www.rubydoc.info/gems/rack-test/0.6.3/Rack/Test/Session#get-instance_method