For these cases, you can run the hook just once for the entire suite of specs or once per example group. Hooks take a :suite or :context argument to modify the scope.

In the following snippet, we use a before(:context) hook to launch a web browser just once for an example group:

07-structuring-code-examples/04/before_and_after_hooks_spec.rb

```
RSpec.describe 'Web interface to my thermostat' do
  before(:context) do
    WebBrowser.launch
  end

  after(:context) do
    WebBrowser.shutdown
  end
end
```

Use :context Hooks Cautiously



We only consider using :context hooks for side effects—such as launching a web browser—that satisfy both of the following two conditions:

- Does not interact with things that have a per-example lifecycle
- Is noticeably slow to run

When you use a :context hook, you're responsible for cleaning up any resulting state—otherwise, it can cause other specs to pass or fail incorrectly.

This is a particularly common problem with database code. Any records created in a before(:context) hook will not run in your per-example database transactions. The records will stick around after the example group completes, potentially affecting later specs.

Sometimes, you need a way to run a piece of setup code just once, before the first example begins. That's what :suite hooks are for:

07-structuring-code-examples/04/spec/spec_helper.rb

```
require 'fileutils'

RSpec.configure do |config|
  config.before(:suite) do
    # Remove leftover temporary files
    FileUtils.rm_rf('tmp')
  end
end
```