To test a second implementation of this interface—such as a disk-backed FileKVStore—you could copy and paste the entire spec and replace all occurrences of HashKVStore with FileKVStore. But then you'd have to add any new common behavior to both spec files. We'd have to manually keep the two spec files in sync.

This is exactly the kind of duplication that shared example groups can help you fix. To make the switch, move your describe block into its own file in spec/support, change it to a shared_examples block taking an argument, and use that argument in the let(:kv_store) declaration:

07-structuring-code-examples/11/shared_examples/spec/support/kv_store_shared_examples.rb

```
RSpec.shared_examples 'KV store' do |kv_store_class|
  let(:kv_store) { kv_store_class.new }

  it 'allows you to fetch previously stored values' do
    kv_store.store(:language, 'Ruby')
    kv_store.store(:os, 'linux')

    expect(kv_store.fetch(:language)).to eq 'Ruby'
    expect(kv_store.fetch(:os)).to eq 'linux'
  end

  it 'raises a KeyError when you fetch an unknown key' do
    expect { kv_store.fetch(:foo) }.to raise_error(KeyError)
  end
end
```

By convention, shared examples go in spec/support; we've named this file kv_store_shared_examples.rb after the common interface we're testing.

The block argument, kv_store_class, will come from the calling code (which we'll see in a moment). Here, it represents the class we're testing.

Conventions Are There for a Reason



When we suggest names and locations for support files, we're not just being fussy. Choosing the right name can help you avoid errors. We've seen people name their support files something like shared_spec.rb—which RSpec will attempt to load as a regular spec file, resulting in warning messages.

Now, you can replace your original spec file with a much simpler one:

07-structuring-code-examples/11/shared_examples/spec/hash_kv_store_spec.rb

```
require 'hash_kv_store'
require 'support/kv_store_shared_examples'

RSpec.describe HashKVStore do
  it_behaves_like 'KV store', HashKVStore
end
```