We're explicitly passing the HashKVStore implementation class when we bring in the shared examples with it_behaves_like. The shared_examples block from the previous snippet uses this class in its let(:kv_store) declaration.

Nesting

In the introduction to this section, we mentioned that you can include shared examples with either include_examples or it_behaves_like call. So far, we've just used it_behaves_like. Let's talk about the difference between the two calls. Here's a version of the snippet with include_examples instead:

07-structuring-code-examples/11/shared_examples/spec/include_examples_spec.rb

```
RSpec.describe HashKVStore do
  include_examples 'KV store', HashKVStore
end
```

The spec would behave just fine, but problems creep in if we add a second call to include_examples:

07-structuring-code-examples/11/shared_examples/spec/include_examples_twice_spec.rb

```
RSpec.describe 'Key-value stores' do
  include_examples 'KV store', HashKVStore
  include_examples 'KV store', FileKVStore
end
```

Calling include_examples is like pasting everything in the shared example group directly into this describe block. In particular, you'd get two let declarations for :kv_store: one for HashKVStore and one for FileKVStore. One would overwrite the other. The documentation output shows how they are stepping on each other's toes:

```
$ rspec spec/include_examples_twice_spec.rb --format documentation

Key-value stores
  allows you to fetch previously stored values
  raises a KeyError when you fetch an unknown key
  allows you to fetch previously stored values
  raises a KeyError when you fetch an unknown key

Finished in 0.00355 seconds (files took 0.10257 seconds to load)
4 examples, 0 failures
```

Using it_behaves_like avoids this issue:

07-structuring-code-examples/11/shared_examples/spec/it_behaves_like_twice_spec.rb

```
RSpec.describe 'Key-value stores' do
  it_behaves_like 'KV store', HashKVStore
  it_behaves_like 'KV store', FileKVStore
end
```

Here, each example group gets nested into its own context. You can see the difference when you run with the --format documentation option to RSpec: