Exercise

In this exercise, you've inherited specs for two different URI parsers. The implementations have similar, but not identical, behavior. Your task will be to figure out what the common functionality is, and then extract it to shared specs using the techniques in this chapter. First, here's a spec file for Ruby's built-in URI library:

07-structuring-code-examples/exercises/shared_examples_exercise/spec/uri_spec.rb

```
require 'uri'

RSpec.describe URI do
  it 'parses the host' do
    expect(URI.parse('http://foo.com/').host).to eq 'foo.com'
  end

  it 'parses the port' do
    expect(URI.parse('http://example.com:9876').port).to eq 9876
  end

  it 'defaults the port for an http URI to 80' do
    expect(URI.parse('http://example.com/').port).to eq 80
  end

  it 'defaults the port for an https URI to 443' do
    expect(URI.parse('https://example.com/').port).to eq 443
  end
end
```

Next, here's one for Addressable, an alternative to URI that's more standards-compliant:[6]

07-structuring-code-examples/exercises//shared_examples_exercise/spec/addressable_spec.rb

```
require 'addressable'

RSpec.describe Addressable do
  it 'parses the scheme' do
    expect(Addressable::URI.parse('https://a.com/').scheme).to eq 'https'
  end

  it 'parses the host' do
    expect(Addressable::URI.parse('https://foo.com/').host).to eq 'foo.com'
  end

  it 'parses the port' do
    expect(Addressable::URI.parse('http://example.com:9876').port).to eq 9876
  end

  it 'parses the path' do
    expect(Addressable::URI.parse('http://a.com/foo').path).to eq '/foo'
  end
end
```

6. https://github.com/sporkmonger/addressable