```
« truncated »
 :shared_group_inclusion_backtrace=>[],
 :last_run_status=>"unknown"}
.

Finished in 0.00279 seconds (files took 0.09431 seconds to load)
1 example, 0 failures
```

Even before we've defined any metadata, RSpec has attached plenty of its own! Most of the keys in this hash are self-explanatory, but a few merit a closer look:

:description
: Just the string we passed to it; in this case, "is used by RSpec..."

:full_description
: Includes the text passed to describe as well; in this case, "Hash is used by RSpec..."

:described_class
: The class we passed to the outermost describe block; also available inside any example via RSpec's described_class method

:file_path
: Directory and filename where the example is defined, relative to your project root; useful for filtering examples by location

:example_group
: Gives you access to metadata from the enclosing example group

:last_run_status
: Will be "passed", "pending", "failed", or "unknown"; the latter value appears if you haven't configured RSpec to record the pass/fail status or if the example has never been run

As you'll see in the coming sections, having this information at runtime will come in handy.

Custom Metadata

You can count on the keys in the previous section to be present in every metadata hash. Other keys may also be present, depending on metadata you've set explicitly. Update metadata_spec.rb to add a fast: true metadata entry:

08-metadata/02/spec/metadata_spec.rb

```
require 'pp'

RSpec.describe Hash do
```