```
➤   it 'is used by RSpec for metadata', fast: true do |example|
      pp example.metadata
    end
  end
```

This particular style of use—passing a key whose value is true, as in fast: true—is so common that RSpec provides a shortcut. You can just pass the key by itself:

08-metadata/03/spec/metadata_spec.rb

```
require 'pp'

RSpec.describe Hash do
➤   it 'is used by RSpec for metadata', :fast do |example|
      pp example.metadata
    end
  end
```

In either case, when you run this spec, you should see :fast=>true in the pretty-printed output.

You can even pass multiple keys:

08-metadata/04/spec/metadata_spec.rb

```
require 'pp'

RSpec.describe Hash do
➤   it 'is used by RSpec for metadata', :fast, :focus do |example|
      pp example.metadata
    end
  end
```

You'll see both :fast=>true and :focus=>true when you run this example.

Finally, when you set custom metadata on an example group, the contained examples and nested groups will inherit it:

08-metadata/04/spec/metadata_inheritance_spec.rb

```
require 'pp'

➤ RSpec.describe Hash, :outer_group do
    it 'is used by RSpec for metadata', :fast, :focus do |example|
      pp example.metadata
    end

➤   context 'on a nested group' do
➤     it 'is also inherited' do |example|
➤       pp example.metadata
➤     end
➤   end
  end
```

As you'd expect, these specs will print :outer_group=>true twice—once for the example in the outer group, and once for the example in the inner group.