08-metadata/07/aggregate_failures.rb
```
RSpec.describe 'Billing', aggregate_failures: false do
  context 'using the fake payment service' do
    before do
      expect(MyApp.config.payment_gateway).to include('sandbox')
    end

    # ...
  end
end
```

Even though aggregate_failures is set to false here, it's getting overridden by the global setting. That means that if one of your examples is accidentally configured to talk to the real payment gateway (instead of the sandbox), the before hook won't stop it.

The fix is easy: in your call to define_derived_metadata, check to see if the key exists first before overriding it:

08-metadata/08/spec/spec_helper.rb
```
RSpec.configure do |config|
  config.define_derived_metadata do |meta|
    meta[:aggregate_failures] = true unless meta.key?(:aggregate_failures)
  end
end
```

Now, you're able to set the flag globally, but still switch it off for individual cases where you don't want that behavior.

Next, let's talk about how to access metadata and put it to good use.

Reading Metadata

Take one more peek at the it block you wrote at the start of the chapter:

08-metadata/08/spec/metadata_spec.rb
```
it 'is used by RSpec for metadata' do |example|
  pp example.metadata
end
```

As this snippet shows, RSpec hands your block an example argument, from which you can read the metadata. RSpec passes the same kind of block argument in hooks marked as having :example scope:

08-metadata/09/around_hook.rb
```
RSpec.configure do |config|
  config.around(:example) do |example|
    pp example.metadata
  end
end
```