--only-failures

Any time you have failed specs, those are usually the ones you want to focus your attention on. This option makes it easy to rerun just the failures.

--next-failure

A more surgical form of --only-failures, this option is nice when you want to fix and test each failure one by one.

--example 'part of a description'

This option comes in handy when you want to run a particular example or group, and you can remember part of the description but not what line it's on.

--tag tag_name

If you carefully tag your examples and groups with appropriate metadata, this powerful option will let you run arbitrary cross-sections of your suite.

By running exactly the specs you need, you minimize how long you have to wait to get feedback on your code changes.

Output Options

Different situations call for different levels of detail in your test suite output. Elsewhere in the --help text, you'll see a number of output options:

```
**** Output ****
  -f, --format FORMATTER            Choose a formatter.
                                      [p]rogress (default - dots)
                                      [d]ocumentation (group and example ↩
                                         names)
                                      [h]tml
                                      [j]son
                                      custom formatter class name
  -o, --out FILE                    Write output to a file instead of ↩
                                    $stdout. This option applies to the ↩
                                    previously specified --format, or the ↩
                                    default format if no format is ↩
                                    specified.
      --deprecation-out FILE        Write deprecation warnings to a file ↩
                                    instead of $stderr.
  -b, --backtrace                   Enable full backtrace.
      --force-color, --force-colour Force the output to be in color, even ↩
                                    if the output is not a TTY
      --no-color, --no-colour       Force the output to not be in color, ↩
                                    even if the output is a TTY
  -p, --[no-]profile [COUNT]        Enable profiling of examples and list ↩
                                    the slowest examples (default: 10).
```