```
.F

  2) Another group with a failure has an example that fails
     Failure/Error: expect(1).to eq 2

       expected: 2
            got: 1

       (compared using ==)
     # ./a_spec.rb:13:in `block (2 levels) in <top (required)>'

.

Finished in 0.0307 seconds (files took 0.08058 seconds to load)
4 examples, 2 failures

Failed examples:

rspec ./a_spec.rb:2 # A group with a failure has an example that fails
rspec ./a_spec.rb:12 # Another group with a failure has an example that fails
```

RSpec used its default progress formatter (with dots for passing specs and `F` for failing ones). But check out where the first failure message appears: after the `F` but before the dot marking the second example. Thanks to the new custom formatter, RSpec is printing failures as soon as they happen.

The new formatter also works with RSpec's built-in documentation formatter:

```
$ rspec a_spec.rb --format doc

A group with a failure
  has an example that fails (FAILED - 1)

  1) A group with a failure has an example that fails
     Failure/Error: expect(1).to eq 2

       expected: 2
            got: 1

       (compared using ==)
     # ./a_spec.rb:3:in `block (2 levels) in <top (required)>'

  has an example that succeeds

Another group with a failure
  has an example that fails (FAILED - 2)

  2) Another group with a failure has an example that fails
     Failure/Error: expect(1).to eq 2

       expected: 2
            got: 1

       (compared using ==)
```