09-configuring-rspec/04/configuring_rspec/mocha_spec.rb
```
RSpec.configure do |config|
  config.mock_with :mocha
end

RSpec.describe 'config.mock_with :mocha' do
  it 'allows you to use mocha instead of rspec-mocks' do
    item = stub('Book', cost: 17.50)

    credit_card = mock('CreditCard')
    credit_card.expects(:charge).with(17.50)

    PointOfSale.purchase(item, with: credit_card)
  end
end
```

RSpec also supports the :rr and :flexmock mocking libraries.[9,10]

You can pass a block to mock_with to set options for the mocking library. In the following snippet, we turn on some extra verification in rspec-mocks:

09-configuring-rspec/04/configuring_rspec/rspec_mocks_configuration_spec.rb
```
RSpec.configure do |config|
  config.mock_with :rspec do |mocks|
    mocks.verify_partial_doubles = true
    mocks.verify_doubled_constant_names = true
  end
end
```

We'll talk more about configuring your test doubles in *Using Partial Doubles Effectively*, on page 271. In case you're curious, here's what these two options do:

mocks.verify_partial_doubles = true

Verifies that each *partial double*—a normal object that has been partially modified with test double behavior—conforms to the object's original interface.

mocks.verify_doubled_constant_names = true

When creating a verifying double using a string such as "SomeClassName", RSpec will verify that SomeClassName actually exists.

The full configuration docs for rspec-mocks are available online.[11]

Expectations

Just as mock_with lets you configure an alternative to rspec-mocks, expect_with lets you choose a different assertion framework instead of rspec-expectations:

9. http://rr.github.io/rr/
10. https://github.com/doudou/flexmock
11. http://rspec.info/documentation/3.6/rspec-mocks/RSpec/Mocks/Configuration.html